



Introducing Classic Series II Speakers

Classic Boston Performance

Classic Boston Styling

Classic Boston Value



Classic Boston speakers, Classic Boston value

Classic Series II was designed to offer Boston's legendary sound, classic look, exceptional quality, and value. Classic loudspeakers provide an excellent foundation for a multi-channel home theater system or a stereo-only music system. The Classic Series II includes a high performance floorstanding loudspeaker, two bookshelf loudspeakers, a center channel, a 100-watt powered subwoofer, and a satellite/center loudspeaker package. All Classic models are finished in Black Walnut Vinyl - a classic look that looks great anywhere.

Key features

- Boston Kortec® soft dome tweeters for crystalline high-frequency sound
- Graphite injected polymer woofers utilize Deep Channel® Design (DCD) for more bass from less amplifier power
- Acoustically tuned port for improved bass
- MagnaGuard® magnetic shielding prevents video interference
- 5-way gold-plated binding posts for hook-up flexibility and the purest signal transfer





Available now.

CS 260 II

Dual 6½" 2-Way Floorstanding Speaker



CS 225C II

Dual 5¼" 2-Way Center Channel Speaker



CS 26 II and 23 II

CS 26 II 2-Way 6½" Bookshelf Speaker

CS 23 II 2-Way 3½" Bookshelf Speaker



CS 2300 II System

(4) CS 23 II 2-Way 3½" Bookshelf Speakers

(1) CS 223C II Dual 3½" 2-Way Center Channel Speaker



CS Sub10 II

100 Watt 10" Down-firing DCD Subwoofer

Specifications	CS 23 II	CS 26 II	CS 223C II*	CS 225C II	CS 260 II
Frequency Range (±3dB)	120Hz – 20kHz	52Hz – 25kHz	100Hz – 20kHz	80Hz – 25kHz	46Hz – 25kHz
Recommended Amplifier	10 – 150 watts	10 – 150 watts	15 – 150 watts	15 – 175 watts	15 – 250 watts
Sensitivity	89dB [SPL/2.8V at 1m]	89dB [SPL/2.8V at 1m]	89dB [SPL/2.8V at 1m]	89dB [SPL/2.8V at 1m]	89dB [SPL/2.8V at 1m]
Nominal Impedance	8 ohms	8 ohms	8 ohms	8 ohms	8 ohms
Crossover Frequency	3,200Hz	3,000Hz	3,000Hz	2,800Hz	2,800Hz
Woofers	3½" (89mm) DCD Graphite injected polymer woofer	6½" (165mm) DCD Graphite injected polymer woofer	Dual 3½" (89mm) DCD Graphite injected polymer woofer	Dual 5¼" (133mm) DCD Graphite injected polymer woofer	Dual 6½" (165mm) DCD Graphite injected polymer woofer
Passive Radiators	—	—	—	—	—
High-Frequency Driver	1" (25mm) Kortec® Soft Dome	1" (25mm) Kortec Soft Dome	1" (25mm) Kortec Soft Dome	1" (25mm) Kortec Soft Dome	1" (25mm) Kortec Soft Dome
Dimensions (H x W x D)	7 ¹¹ / ₁₆ x 4 ¹¹ / ₁₆ x 5 ⁵ / ₁₆ " (194 x 118 x 135mm)	12 ¹ / ₄ x 9 ³ / ₄ " x 7 ¹¹ / ₁₆ " (310 x 246 x 194mm)	5 x 11 ⁵ / ₈ x 5 ¹ / ₂ " (127 x 294 x 140mm)	6 ⁵ / ₈ x 16 ⁵ / ₁₆ x 8 ⁵ / ₁₆ " (167 x 414 x 210mm)	38 ¹ / ₄ x 7 ¹¹ / ₁₆ x 12 ³ / ₄ " (972 x 194 x 322mm)
Weight:	3 lbs (1.45Kg)	10 lbs (4.45Kg)	7 lbs (3Kg)	13 lbs (6Kg)	27 lbs (12.3Kg)

* Only available in CS 2300 II System

Specifications	CS Sub10 II
Frequency Range	35 – 150 Hz
Amplifier Power	100 watts RMS; BassTrac® circuitry eliminates distortion
Bass Driver	10" (254mm) DCD
Dimensions (H x W x D)	16 x 15 x 15" (406 x 381 x 381mm)
Weight:	26 lbs (12kg)

Boston Acoustics continually strives to update and improve its products.
The specifications and construction details are subject to change without notice.



300 Jubilee Drive, Peabody, MA 01960 bostonacoustics.com

© 2011 All rights reserved. Boston, Boston Acoustics, BassTrac, Deep Channel, Kortec, the B/A ellipse symbol, and MagnaGuard are registered trademarks of Boston Acoustics, Inc.